

## Delivery specifications

### The document

- The cutting die drawing supplied by Total Packaging serves as the starting point in manufacturing the artwork.  
This cutting die drawing is normative and may absolutely not be adjusted.
- The specified registration colours must be implemented in the artwork.
- Leave fitted crosses, cutting symbols and registration block (if shown in the drawing) in 'Registration colour'.
- The cutting die drawing used (spot colours) is not to be included in the artwork.
- Convert ink and varnish notches (indicate in spot colour) to white -> C=0 M=0 Y=0 K=0, or leave blank in the artwork.
- The resolution must be at least 300 dpi for images. Do ensure that these resolutions apply to the size that is used in the layout.
- Images and files are to be supplied in CMYK and/or PMS colours.
- Document is to be supplied on 1 page with cutting symbols, fitted crosses and registration block (in registration colour) and at least 3 mm overfill.
- All of the fonts used (screen- and printer fonts, as well as the fonts used in the EPS-files) must be enclosed in the PDF and/or supplied.
- Printing files are to be delivered without trapping.
- The maximum ink coverage to prevent stains is 280%. (The ink coverage is the total percentage of colour that you use in your colour build-up).

### Programmes

Documents received as PDF (PDF, Adobe Acrobat DC)

### Adaptation printing result

We can print out colour-fast Epson proofs with a predictable result for the printing presses. The Epson proofs come close to the PMS colours, we use a calibrated PMS spectrum when printing. If no stamped, colour-fast prints and/or proofs are delivered, then the 4 primary colours will be run on standard densities, PMS colours in accordance to the calibrated PMS colour spectrum.

### File Transfer

- E-mail: see contact information, or the appropriate colleague in the sales department. Data limit plus minus 10MB
- Wetransfer [www.wetransfer.com](http://www.wetransfer.com) / Data limit 2GB

### Technical Specifications

- |                                    |                        |
|------------------------------------|------------------------|
| - Printing process:                | Offset                 |
| - Number of colours in 1 passage:  | 5 + dispersion lacquer |
| - Total ink coverage area:         | 280%                   |
| - Minimal line thickness positive: | 0.12 mm                |
| - Minimal line thickness negative: | 0.18 mm                |
| - Positive text (sanserif):        | 4 ptn                  |
| - Positive text (with serif):      | 5 ptn                  |
| - Negative text (sanserif):        | 6 ptn                  |
| - Negative text (with serif):      | 7 ptn                  |
| - Overfill:                        | 3.0 mm                 |
| - Minimal size Bar code:           | 80%                    |

Should you have any questions after the method of delivery, then please contact us.